
CHAPTER 542
Regulations for Antennas

542.1 Ground-mounted, freestanding
antennas.

542.2 Roof-mounted Antennas.
542.3 Signs Prohibited.

Sec. 542.1 GROUND-MOUNTED, FREESTANDING ANTENNAS.

- A. Location: Any type of ground-mounted, freestanding antenna shall not be located within fifteen (15) feet of the main building; shall not be built within twenty (20) feet of the side and rear lot lines and shall not be erected in the front yard.
- B. Height:
 - 1. Ground-mounted, freestanding antennas exceeding three (3) feet in diameter shall not exceed a height of fifteen (15) feet, above grade level, including the mounting structure.
 - 2. Ground-mounted, freestanding antennas not exceeding three (3) feet in diameter and antennas consisting of wires, poles, rods, etc. including any mounting structure shall not exceed a height of thirty-five (35) feet above grade level.
- C. Zoning Certificate: Ground-mounted, freestanding antennas are considered structures and require a zoning certificate.

Sec. 542.2 ROOF-MOUNTED ANTENNAS.

- A. Height and Size:
 - 1. Roof-mounted antennas shall not exceed three (3) feet in diameter and shall not exceed the roof height of the building upon which it is mounted by more than four (4) feet.
 - 2. All other types of mounted antennas, consisting of wires, rods, poles, etc., shall not exceed the roof height of the building upon which it is mounted by more than ten (10) feet.

Sec. 542.3 SIGNS PROHIBITED.

- A. An antenna shall not function as a sign in any way.

